

DIN 7985 ähnlich ISO 7045
Linsenschrauben

Kreuzschlitz H (Phillips)

Stahl 4.8 | verzinkt | Cr(VI) - frei | Metrisches Gewinde

Hinweis: DIN-Norm wurde zurückgezogen | geänderte Kopfhöhe



Durchmesser (d)	a max.	d _a max.	d _k min.	d _k max.	Nennmaß	k min.	k max.	r _f	r max.	Steigung (P)	v	Werkzeuggröße
M2	0,8	2,6	3,70	4	1,6	1,48	1,72	4	0,10	0,40	1,1	H1
M2,5	0,9	3,1	4,70	5	2,0	1,88	2,12	5	0,10	0,45	1,3	H1
M3	1,0	3,6	5,70	6	2,4	2,28	2,52	6	0,10	0,50	1,6	H1
M3,5	1,2	4,1	6,64	7	2,7	2,52	2,82	7	0,20	0,60	1,9	H2
M4	1,4	4,7	7,64	8	3,1	2,95	3,25	8	0,20	0,70	2,0	H2
M5	1,6	5,7	9,64	10	3,8	3,65	3,95	10	0,20	0,80	2,5	H2
M6	2,0	6,8	11,57	12	4,6	4,45	4,75	12	0,25	1,00	3,0	H3
M8	2,5	9,2	15,57	16	6,0	5,85	6,15	16	0,40	1,25	3,7	H4

Nennmaß	Länge (l)	
	min.	max.
3	2,80	3,20
4	3,75	4,25
5	4,75	5,25
6	5,75	6,25
8	7,70	8,30
10	9,70	10,30
12	11,65	12,35
14	13,65	14,35

Nennmaß	Länge (l)	
	min.	max.
16	15,65	16,35
18	17,65	18,35
20	19,60	20,40
22	21,60	22,40
25	24,60	25,40
28	27,60	28,40
30	29,60	30,40
35	34,50	35,50

Nennmaß	Länge (l)	
	min.	max.
40	39,50	40,50
45	44,50	45,50
50	49,50	50,50
55	54,00	56,00
60	59,00	61,00
70	69,00	71,00
80	79,00	81,00

Durchmesser (d)	Länge (l)																						
	3	4	5	6	8	10	12	14	16	18	20	22	25	28	30	35	40	45	50	55	60	70	80
M2		●	●	●	●	●	●		●														
M2,5	●	●	●	●	●	●	●	●	●		●		●										
M3		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●				●			
M3,5				●	●								●										
M4		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
M5				●	●	●	●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●
M6					●	●	●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●
M8						●	●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●

• Kombinationen im eShop erhältlich | Weitere Größen auf Anfrage

Alle technischen Daten beziehen sich auf das Maß mm

