

## HELICOIL® Plus installation mandrels with depth stop

for processing of HELICOIL® Plus Screwlock with installation tools types: B-S 824 | E-S 410 | P-S 412 | P-S 1216

Type 4160.25 installation mandrel with depth stop to process HELICOIL® Plus Screwlock coil thread inserts with fine or coarse thread.



**Suited for:**

- Type E-S 410 electrical installation tool
- Type B-S 824 cordless installation tool
- P-S 412 and P-S 1216 pneumatic installation tools

**Properties:**

- With external hexagon as per DIN 3126 – E 6.3/DIN ISO 1173

**Note:**

These installation mandrels can also be used as manual installation mandrels.

HELICOIL® Plus Screwlock installation mandrels are marked with a ring groove on the guide shaft. HELICOIL® Plus Free Running installation mandrels have a smooth guide shaft.

Technical information can be found on the last page.

Diameter (d)	Article number	Pitch (P)	Design
M 7	41602507022	1.00	HELICOIL® Plus Screwlock
M 8	41602508022	1.25	HELICOIL® Plus Screwlock
M 10	41602510022	1.50	HELICOIL® Plus Screwlock
M 12	41602512022	1.75	HELICOIL® Plus Screwlock
M 12x1.5	41602512422	1.50	HELICOIL® Plus Screwlock
M 14	41602514022	2.00	HELICOIL® Plus Screwlock
M 14x1.5	41602514422	1.50	HELICOIL® Plus Screwlock
M 16	41602516022	2.00	HELICOIL® Plus Screwlock
M 16x1.5	41602516422	1.50	HELICOIL® Plus Screwlock
M 18	41602518022	2.50	HELICOIL® Plus Screwlock
M 20	41602520022	2.50	HELICOIL® Plus Screwlock
M 24	41602524022	3.00	HELICOIL® Plus Screwlock

All technical data refer to the measure mm



## HELICOIL® Plus thread inserts



W and  $d_1$  are the control values for thread inserts (Free Running and Screwlock) before they have been installed. The length can only be measured for installed thread inserts.

### Holding thread



### Assembly



tang not broken off

Prior to tapping, counter-bore 90° and deburr.  
Outside diameter of countersink =  $D_{HC} + 0.1 \text{ mm}$ .

- d = Nominal thread diameter
- P = Thread pitch
- $d_1$  = Outside diameter of thread insert prior to installation
- W = Number of threads prior to installation
- $D_{HC}$  = Outside diameter of the parent thread
- $D_{1HC}$  = Crest diameter
- B = Suitable twist drill diameter. Please note:  $D_{1HC}$  is critical for selecting the correct twist drill diameter.
- $t_1$  = Minimum depth of tapped hole according to DIN 76 – Part 1 (guide value)
- $t_2$  = The nominal length of the thread insert corresponds to the minimum length of the full parent thread for blind holes or the minimum plate thickness for a through hole.
- $t_3$  = Maximum screw-in depth when the tang is not removed
- $t_5$  = Distance of the thread insert from the joint face = 0.25 to 0.5 P, if  $t_2$  corresponds to the above-mentioned minimum value

When you use HELICOIL® Plus thread inserts for volume production, we recommend to add at least  $1 \times P$  to values  $t_1$  and  $t_2$ .

All technical data refer to the measure mm

