

HELICOIL® machine taps

straight fluted | For through holes

Type 0141.1 HELICOIL® machine tap to create holding threads for HELICOIL® thread inserts with metric normal and fine screw threads as per DIN 8140-2. The tap is suited for through holes and blind holes with a deeper tap hole.



Properties:

- Straight-fluted
- With spiral point
- 4-pitch chamfer
- 10 % cutting angle
- For materials with 850 N/mm² strength max.
- Tolerance class 5H (6H mod.)

Technical information can be found on the last page.

Diameter (d)	Article number	Version	Pitch (P)	D _{HC} min.	d ₂ nominal size	d ₃ nominal size	d ₄	L ₁	L ₂	L ₃	L ₄	K
M 2	01411020104	A	0.40	2.5	2.8	2	–	50	8	5	–	2.1
M 2.5	01411250104	B	0.45	3.1	3.5	2.5	2.6	56	11	6	18	2.7
M 3	01411030104	B	0.50	3.7	4	3	3.1	56	13	6	20	2.7
M 3.5	01411350104	B	0.60	4.3	4.5	3.5	3.6	63	13	6	21	3.1
M 4	01411040104	B	0.70	4.9	6	4	4.2	70	16	8	25	4.9
M 5	01411050104	B	0.80	6.0	6	5	5.2	80	17	8	30	4.9
M 6	01411060104	B	1.00	7.3	8	6	6.2	90	20	9	35	6.2
M 7	01411070104	B	1.00	8.3	9	7	7.2	90	20	10	35	7.0
M 8	01411080104	B	1.25	9.6	10	8	8.3	100	20	11	39	8.0
M 8x1	01411083104	B	1.00	9.3	9	8	8.2	90	20	10	35	7.0
M 9	01411090104	B	1.25	10.6	8	9	–	100	22	9	–	6.2
M 10	01411100104	C	1.50	12.0	9	10	–	110	24	10	–	7.0
M 10x1	01411103104	C	1.00	11.3	9	10	–	100	22	10	–	7.0
M 10x1.25	01411109104	C	1.25	11.6	9	10	–	100	22	10	–	7.0
M 11	01411110104	C	1.50	13.0	11	11	–	100	22	11	–	9.0
M 12	01411120104	C	1.75	14.3	11	12	–	110	26	12	–	9.0
M 12x1	01411123104	C	1.00	13.3	11	12	–	100	22	12	–	9.0
M 12x1.25	01411129104	C	1.25	13.6	11	12	–	100	22	12	–	9.0
M 12x1.5	01411124104	C	1.50	14.0	11	12	–	100	22	12	–	9.0
M 14	01411140104	C	2.00	16.6	12	14	–	110	28	12	–	9.0
M 14x1	01411143104	C	1.00	15.3	12	14	–	100	22	12	–	9.0
M 14x1.25	01411149104	C	1.25	15.6	12	14	–	100	22	12	–	9.0
M 14x1.5	01411144104	C	1.50	16.0	12	14	–	100	22	12	–	9.0
M 16	01411160104	C	2.00	18.6	14	16	–	125	34	14	–	11.0
M 16x1.5	01411164104	C	1.50	18.0	14	16	–	110	25	14	–	11.0
M 18	01411180104	C	2.50	21.3	16	18	–	140	34	15	–	12.0
M 18x1.5	01411184104	C	1.50	20.0	16	18	–	125	25	15	–	12.0
M 18x2	01411185104	C	2.00	20.6	16	18	–	140	34	15	–	12.0
M 20	01411200104	C	2.50	23.3	18	20	–	140	34	17	–	14.5
M 20x1.5	01411204104	C	1.50	22.0	18	20	–	125	25	17	–	14.5
M 22	01411220104	C	2.50	25.3	18	22	–	160	38	17	–	14.5
M 22x1.5	01411224104	C	1.50	24.0	18	22	–	140	28	17	–	14.5
M 24	01411240104	C	3.00	27.9	20	24	–	160	38	19	–	16.0
M 24x1.5	01411244104	C	1.50	26.0	18	24	–	140	28	17	–	14.5

All technical data refer to the measure mm



HELICOIL® machine taps


straight fluted | For through holes

Diameter (d)	Article number	Version	Pitch (P)	D _{HC} min.	d ₂ nominal size	d ₃ nominal size	d ₄	L ₁	L ₂	L ₃	L ₄	K
M 24x2	01411245104	C	2.00	26.6	20	24	–	140	28	19	–	16.0
M 26x1.5	01411264104	C	1.50	28.0	20	26	–	140	28	19	–	16.0
M 27	01411270104	C	3.00	30.9	22	27	–	180	50	21	–	18.0
M 27x1.5	01411274104	C	1.50	29.0	22	27	–	150	28	21	–	18.0
M 28x1.5	01411284104	C	1.50	30.0	22	28	–	150	28	21	–	18.0
M 30	01411300104	C	3.50	34.5	28	30	–	200	56	25	–	22.0
M 30x1.5	01411304104	C	1.50	32.0	22	30	–	150	28	21	–	18.0
M 30x2	01411305104	C	2.00	32.6	25	30	–	160	30	23	–	20.0
M 33	01411330104	C	3.50	37.5	28	33	–	200	56	25	–	22.0
M 33x2	01411335104	C	2.00	35.6	28	33	–	170	30	25	–	22.0
M 36	01411360104	C	4.00	41.2	32	36	–	200	60	27	–	24.0
M 36x2	01411365104	C	2.00	38.6	32	36	–	170	30	27	–	24.0
M 36x3	01411366104	C	3.00	39.9	32	36	–	200	60	27	–	24.0

All technical data refer to the measure mm




HELICOIL® Plus thread inserts






W and d_1 are the control values for thread inserts (Free Running and Screwlock) before they have been installed. The length can only be measured for installed thread inserts.

Holding thread



Assembly



tang not broken off

Prior to tapping, counter-bore 90° and deburr.
Outside diameter of countersink = $D_{HC} + 0.1 \text{ mm}$.

- d = Nominal thread diameter
- P = Thread pitch
- d_1 = Outside diameter of thread insert prior to installation
- W = Number of threads prior to installation
- D_{HC} = Outside diameter of the parent thread
- D_{1HC} = Crest diameter
- B = Suitable twist drill diameter. Please note: D_{1HC} is critical for selecting the correct twist drill diameter.
- t_1 = Minimum depth of tapped hole according to DIN 76 – Part 1 (guide value)
- t_2 = The nominal length of the thread insert corresponds to the minimum length of the full parent thread for blind holes or the minimum plate thickness for a through hole.
- t_3 = Maximum screw-in depth when the tang is not removed
- t_5 = Distance of the thread insert from the joint face = 0.25 to 0.5 P, if t_2 corresponds to the above-mentioned minimum value

When you use HELICOIL® Plus thread inserts for volume production, we recommend to add at least $1 \times P$ to values t_1 and t_2 .

All technical data refer to the measure mm

